



Catalogue

FOOD SERVICE

Chapter

REFRIGERATION

Specific model

CCP-2G C CI 230V 1N 50Hz

19089831 24/01/2024

DENOMINATION:

Refrigerated counter - Concept 700 Gastronorm with 2 doors, at 50Hz.

DESCRIPTION:

- Structure built with AISI-304 stainless steel
- 50 mm, 40 kg/m3 injected polyurethane insulation.
- Forced draught cooling system inside the room.
- Copper piping and aluminium flaps evaporator.
- Digital display for electronic and digital control of temperature and defrosting.
- The controls are integrated in the front panel for a better protection against dirt. IPX5 compliant, the controls are protected against water splash and lets.
- Easier loading and unloading thanks to its door self-closing and stay open features.
- Removable and height adjustable plastic covered steel shelves for easy cleaning (GN1/1 size).
- Equipment per door: 1 GN 1/1 grid and 2 sets of height adjustable tray slides.
- Built-in drainage to get rid of waste liquids inside the unit.
- Interior LED lighting (only for models with glass doors).
- Embedded bottom and curved panels inside for easy cleaning and maintenance.
- Height adjustable stainless steel legs.
- 10 cm high splashback.
- Working temperature: from 0 °C to +8 °C (refrigerators) and from -18 °C to -22 °C (freezers).
- -Tested in climatic class IV.

Refrigerated counters.

- Castors included
- UK plug included

POSSIBLE OPTIONS:

- Stainless Backing
- Legs instead of castors
- Without splashback
- Door frame resistance
- Glass door
- Granite worktop
- Drawers [1/2] unit
- Locks
- Left group
- Without breastplate
- Without Countertop
- Panoramic aperture
- Drawers [1/3] unit
- Drawers [1/3 + 2/3] unit

POSSIBLE ACCESSORIES:

- REFRIGERATION
- ACCESSORIES
- ACCESSORIES FOR REFRIGERATION
- GASTRONORM GRIDS

SUPPLIED ACCESSORIES:

- 12035781 GN 1/1 grid in epoxy (530x325) 2



				- t-	
X Width	1342	mm	X Gross width	1465	mm
Y Depth	700	mm	Y Gross depth	825	mm
Z Height	850	mm	Z Gross height	1000	mm
Net Weight	107,0	kg	Gross Weight	112,0	kg
Net volume	0,798	m3	Gross volume	1,200	m3

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,203 kW
Amperage (A)	0,96 A
Voltage	230V - 1N
Electric frequency	50Hz

GAS TECHNICAL SPECIFICATIONS

Gas type R-600a

COLD TECHNICAL SPECIFICATIONS

Refrigeration power

Energy Efficiency Index

Annual elec. consumption	752,00 kWh
Power consumption 24h	2,06 kWh
Gross internal volume	274 L
Refrigeration net.vol	143 L
Climate class	4
Cooling gas load	64,000 g
Clasif. Energy efficiency	В

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring 2X1+T-2A

OTHERS

Model Type

Number of doors 2
Condensation system Vent.











0,361 kW

34 89 %

Counter Cabinet





Catalogue

FOOD SERVICE

Chapter

REFRIGERATION

Specific model

CCP-2G C CI 230V 1N 50Hz

19089831 24/01/2024

- 12037936 Guide for grill GN-1/1 - wall - 562 mm - 1 piece 8











