



DENOMINATION:

Refrigerated counter - Concept 700 Gastronorm with 4 doors, at 50Hz.

DESCRIPTION:

- Structure built with AISI-304 stainless steel
- 50 mm, 40 kg/m3 injected polyurethane insulation.
- Forced draught cooling system inside the room.
- Copper piping and aluminium flaps evaporator.
- Digital display for electronic and digital control of temperature and defrosting.
- The controls are integrated in the front panel for a better protection against dirt. IPX5 compliant, the controls are protected against water splash and jets.
- Easier loading and unloading thanks to its door self-closing and stay open features.
- Removable and height adjustable plastic covered steel shelves for easy cleaning (GN1/1 size).
- Equipment per door: 1 GN 1/1 grid and 2 sets of height adjustable tray slides.
- Built-in drainage to get rid of waste liquids inside the unit.
- Interior LED lighting (only for models with glass doors).
- Embedded bottom and curved panels inside for easy cleaning and maintenance.
- Height adjustable stainless steel legs.
- 10 cm high splashback.
- Working temperature: from 0 °C to +8 °C (refrigerators) and from -18
- °C to -22 °C (freezers).
- -Tested in climatic class IV.
- Refrigerated counters.
- Castors included.
- UK plug included.

POSSIBLE OPTIONS :

- Stainless Backing
- Legs instead of castors
- Without splashback
- Door frame resistance
- Glass door
 Granite worktop
- Drawers [1/2] unit
- Locks
- Left group
- Without breastplate
- Without Countertop
- Panoramic aperture
- Drawers [1/3] unit
- Drawers [1/3 + 2/3] unit

POSSIBLE ACCESSORIES :

- REFRIGERATION
- ACCESSORIES
- ACCESSORIES FOR REFRIGERATION
- GASTRONORM GRIDS

SUPPLIED ACCESSORIES:

- 12035781 GN 1/1 grid in epoxy (530x325) 4



Catalogue FOOD SERVICE Chapter REFRIGERATION

Specific model CCP-4G C CI 230V 1N 50Hz

19089851

DIMENSIONS

24/01/2024

¢Ζ

				×	
X Width	2242	mm	X Gross width	2 36 5	mm
Y Depth	700	mm	Y Gross depth	825	mm
Z Height	850	mm	Z Gross height	1000	mm
Net Weight	157,0	kg	Gross Weight	166,0	kg
Net volume	1,334	m3	Gross volume	1,941	m3

ELECTRICITY TECHNICAL SPECIFICATIONS

ELECTRICITY TECHNICAE SI ECITICATIONS	
Electric power	0,224 kW
Amperage (A)	1,04 A
Voltage	230V - 1N
Electric frequency	50Hz
GAS TECHNICAL SPECIFICATIONS	
Gas type	R-600a
COLD TECHNICAL SPECIFICATIONS	
Refrigeration power	0,436 kW
Annual elec. consumption	1096,00 kWh
Power consumption 24h	3,00 kWh
Gross internal volume	581 L
Refrigeration net.vol	285 L
Climate class	4
Cooling gas load	108,000 g
Clasif. Energy efficiency	С
Energy Efficiency Index	43,48 %
Model Type	Counter Cabinet
CONNECTIONS TECHNICAL SPECIFICATIONS	
Single-phase 230V wiring	2X1+T-2A
OTHERS	
Number of doors	4
Condensation system	Vent.



