



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUP-11G1/1 230V 1N 50Hz

19089485

23/10/2023

The photo may show the standard model and not the configured one

DENOMINATION:

Refrigerated cabinet - Concept Gastronorm 1/1, at 50Hz.

DESCRIPTION :

- Structure built with AISI-304 stainless steel.
- 60 mm, 40 kg/m³ injected polyurethane insulation.
- Storage trays at 23 different levels 55 mm from each other.
- Forced draught system with cooling unit outside the room and monoblock system to optimise storage capacity.
- Copper piping and aluminium flaps evaporator.
- Digital display for electronic and digital control of temperature and defrosting.
- Opened door delay alarm.
- Self-closing and stay open doors. When opened less than 90° they close by themselves. When opened more than 135° they stay open.
- Built-in drainage to get rid of waste liquids inside the unit.
- Embedded bottom and curved panels inside for easy cleaning and maintenance.
- Height adjustable stainless steel legs.
- Working temperature: from 0 °C to +8 °C (refrigerators) and from -18 °C to -22 °C (freezers).
- Tested in climatic class 4.
- LED interior lighting and power switch.
- Refrigerated cabinet.
- Working temperature: from 0 °C to +8 °C.


POSSIBLE OPTIONS :

- 60 Hz
- Stainless Backing
- Wheels Kit (Factory Assembly)
- British plug
- Door frame resistance
- Glass door
- Locks
- Opposite Opening
- Pedal
- Remote group

POSSIBLE ACCESSORIES :

- ACCESSORIES
- ACCESSORIES FOR REFRIGERATION
- GASTRONORM GRIDS

DIMENSIONS



X Width	490 mm	X Gross width	770 mm
Y Depth	700 mm	Y Gross depth	565 mm
Z Height	2010 mm	Z Gross height	2100 mm
Net Weight	102,0 kg	Gross Weight	115,0 kg
Net volume	1,122 m ³	Gross volume	0,914 m ³

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,205 kW
Amperage (A)	1 A
Voltage	230V - 1N
Electric frequency	50Hz

GAS TECHNICAL SPECIFICATIONS

Gas type	R-600a
----------	--------

COLD TECHNICAL SPECIFICATIONS

Refrigeration power	0,361 kW
Annual elec. consumption	726,40 kWh
Power consumption 24h	1,99 kWh
Refrigeration net.vol	231 L
Climate class	4
Cooling gas load	100,000 g
Clasif. Energy efficiency	D
Energy Efficiency Index	73,40 %
Model Type	Vertical cabinet

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1+T-2A
--------------------------	----------

OTHERS

Number of doors	1
Noise level	53,00 dB
Condensation system	Vent.





Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUP-11G1/1 230V 1N 50Hz

19089485

23/10/2023

