



**Catalogue**  
FOOD SERVICE  
**Chapter**  
REFRIGERATION

**Specific model**  
CUP-22G C CI 230V 1N 50Hz

19090614

23/01/2024

**DENOMINATION:**

Refrigerated cabinet - Concept Gastronorm with 2 compartments and 2 door, at 50Hz.

**DESCRIPTION :**

- Structure built with AISI-304 stainless steel.
  - 60 mm, 40 kg/m<sup>3</sup> injected polyurethane insulation.
  - Embedded inner tray slides. Storage trays at 23 different levels 55 mm from each other.
  - Forced draught cooling system with hermetically sealed compressor.
  - Copper piping and aluminium flaps evaporator.
  - Digital display for electronic and digital control of temperature and defrosting.
  - Opened door delay alarm.
  - Self-closing and stay open doors. When opened less than 90° they close by themselves. When opened more than 135° they stay open.
  - Built-in drainage to get rid of waste liquids inside the unit.
  - Embedded bottom and curved panels inside for easy cleaning and maintenance.
  - Height adjustable stainless steel legs.
  - Working temperature: from 0 °C to +8 °C (refrigerators) and from -18 °C to -22 °C (freezers).
  - Tested in climatic class 4..
  - Inner LED lights with power switch (in refrigerated cabinets and now also in freezing units).
- Refrigerated cabinet
- Castors included
  - UK plug included

**POSSIBLE OPTIONS :**

- Stainless Backing
- Legs instead of castors
- Door frame resistance
- Glass door
- Locks
- Pedal
- Remote group

**POSSIBLE ACCESSORIES :**


- REFRIGERATION
- ACCESSORIES
- GASTRONORM GRIDS

**SUPPLIED ACCESSORIES:**

- 12037936 Guide for grill GN-1/1 - wall - 562 mm - 1 piece 6
- 12037958 GN-2/1 GRID made in Epoxi (650x530) 6

**DIMENSIONS**

|            |                      |                |                      |
|------------|----------------------|----------------|----------------------|
| X Width    | 1318 mm              | X Gross width  | 1430 mm              |
| Y Depth    | 842 mm               | Y Gross depth  | 880 mm               |
| Z Height   | 2040 mm              | Z Gross height | 2063 mm              |
| Net Weight | 227,0 kg             | Gross Weight   | 240,0 kg             |
| Net volume | 2,264 m <sup>3</sup> | Gross volume   | 2,596 m <sup>3</sup> |



**ELECTRICITY TECHNICAL SPECIFICATIONS**

|                    |           |
|--------------------|-----------|
| Amperage (A)       | 0,84 A    |
| Electric frequency | 50Hz      |
| Electric power     | 0,206 kW  |
| Voltage            | 230V - 1N |

**GAS TECHNICAL SPECIFICATIONS**

|          |        |
|----------|--------|
| Gas type | R-600a |
|----------|--------|

**COLD TECHNICAL SPECIFICATIONS**

|                           |                  |
|---------------------------|------------------|
| Annual elec. consumption  | 913,00 kWh       |
| Clasif. Energy efficiency | C                |
| Climate class             | 4                |
| Cooling gas load          | 100,000 g        |
| Energy Efficiency Index   | 45,17 %          |
| Gross internal volume     | 1186 L           |
| Model Type                | Vertical cabinet |
| Power consumption 24h     | 2,50 kWh         |
| Refrigeration net.vol     | 859 L            |
| Refrigeration power       | 0,436 kW         |

**CONNECTIONS TECHNICAL SPECIFICATIONS**

|                          |          |
|--------------------------|----------|
| Single-phase 230V wiring | 2X1+T-2A |
|--------------------------|----------|

**OTHERS**

|                     |       |
|---------------------|-------|
| Condensation system | Vent. |
| Number of doors     | 2     |



**Catalogue**  
FOOD SERVICE  
**Chapter**  
REFRIGERATION

**Specific model**  
CUP-22G C CI 230V 1N 50Hz

19090614

23/01/2024

