



Product Code: HR360

Refrigerated Undercounter Cabinet

---



## Features & Benefits

---

- Front breathing refrigeration system, suitable for use even in enclosed areas
- Easy to use microprocessor control with digital display on the front for easy visual reference
- Stainless steel exterior as standard with aluminium interior
- Roller castors to rear for ease of movement
- Integrated door lock for security
- High quality magnetic door gasket
- Operate in ambient up to 40°C

## External Finish

**s/s ext** Standard

## Internal Finish

**aluminium** Standard

## Shelving

**Nylon Coated Shelf** Option

## Base Fittings

**Levelling Bolts** Standard

## Doors

**Solid** Standard

## Refrigeration

**R290 - Energy Efficient** Standard

## Electrical, Service & Ecodesign Data

**230/50/1** Standard

**Fuse Required** 13

**Global Warming Potential** 3

**Energy Efficiency Index** 40.05

**Refrigerant Charge** 0.150

**kWh (24 hours)** 2.76

## Specification

**Dimensions (Width)** 1217

**Dimensions (Height)** 824

**Dimensions (Depth)** 755

**Weight (Unpacked, kg)** 90.5

**Weight (Packed, kg)** 104.51

**Gross Volume** 360

**Noise DbA @ 1M** TBC

**R134a - Industry Standard** Option

**Integral Refrigeration System** Standard

## Footnotes

- External cabinet depth excludes 25mm door handle
- Note: for airflow, ensure that 25mm clearance is allowed above the cabinet
- Decibel rating measured 1m high from the floor and 1m from the cabinet



## Application

This appliance is intended for use in ambient temperatures up to 40°C

## Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

## Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



Energy



Quality



Value



Design



Hygiene



After Care