

Preparation Units



ICE3800GR 7 x 1/3 GN Pans Included




ICE3850GR 12 x 1/3 GN Pans Included

Features

- Removeable chopping board
- Stainless steel retractable lid covering GN pans
- Bottom mounted compressor units
- Stainless steel interior and exterior construction
- Self-closing and stay open door
- Rounded interior corner design
- Recessed door handle
- Magnetic door gaskets
- 1x shelf + 1x base shelf per door
- Easy access for service
- Castors as standard

| Product Code | |
|--------------|--|
| ICE3800GR | 2 Door Preparation Unit 7 x 1/3 GN Pans Included |
| ICE3850GR | 3 Door Preparation Unit 12 x 1/3 GN Pans Included |

Optional Extras








Preparation Units

ICE3800GR

ICE3850GR







| Classification | ICE3800GR | ICE3850GR |
|---------------------------------------|-----------------------|-----------------------|
| Exterior Dimension (WxDxH mm) | 904 x 700 x 947 | 1369 x 700 x 947 |
| Interior Dimension (WxDxH mm) | 830 x 595 x 510 | 1295 x 595 x 510 |
| Packing Dimension (WxDxH mm) | 945 x 750 x 1050 | 1410 x 750 x 1050 |
| Shelf Dimension (WxDxH mm) | 340 x 590 | 340 x 590 |
| Useable Working Area (mm) | 900 x 135 | 1365 x 135 |
| Shelf Quantity | 4 | 6 |
| Loading Capacity Per Shelf (kg/pcs) | 18 | 18 |
| Capacity (Litre) | 300 | 380 |
| Net Weight (kg) | 70 | 90 |
| Gross Weight (kg) | 90 | 120 |
| Voltage (V/Hz/Ph) | 220/50/1 | 220/50/1 |
| Power (W) | 310 | 310 |
| Electric Current (A) | 2 | 2 |
| Power Consumption (kw/24h) | 2.12 | 2.55 |
| Defrost Method | Air Defrost | Air Defrost |
| Climatic Class | 4 | 4 |
| Refrigerant Amount (g) | 60g | 70g |
| Refrigerant | R600a | R600a |
| Cooling Method | Fan Assisted | Fan Assisted |
| Inner Temperature (°C) | -2ºC to +8ºC | -2ºC to +8ºC |
| Insulation Thickness (mm) | 35 | 35 |
| Foaming Material | C5H10 | C5H10 |
| Castors | 4 (2 Braked on front) | 4 (2 Braked on front) |
| Stainless Steel Interior and Exterior | 201 | 201 |