

SILVERLINK 600



J10/N - Silverlink 600 Natural Gas Freestanding Twin Tank Fryer - 2 Baskets - W 600 mm - 24.0 kW Deliver perfectly crisp on the outside and fluffy on the inside chips time after time with the Silverlink 600 Free Standing Gas Fryer.

- Double tank twin basket operation giving you the flexibility to cook different foods or loads simultaneously, delivering 100 kg of chips an hour
- Front mounted controls for safety
- Thermostatically controlled to give accurate cooking temperatures throughout cooking. Flame failure device and top temperature cut out ensures safe operation.
- Cool zone collects cooking debris gives cleaner cooking results and saves money by prolonging the life of the oil

- Piezo ignition for easy lighting
- Heavy duty nickel plated baskets for the most demanding of operations
- Internal drain off tap for easy removal of cooking

Specifications

Summary Power and Performance Range Name Silverlink 600 **BTU** per Hour 81,880 **Power Type Total Power kW** Gas 24 N Temperature Range °C Gas Type 110 - 190 Natural Gas **Unit Type Temperature Control** Free-standing Mechanical Available in UK Only **UK Warranty** 2 Years Parts and Labour Warranty **Export Warranty** Contact your local dealer **GTIN Code** 5056105105084

| Key Specifications | | Weights and Dimensions | | |
|--------------------|----------|---------------------------|------|--|
| Capacity Litres | 2 x 12.0 | Unit Height (External) mm | 1060 | |
| Number of Baskets | 2 | Unit Width (External) mm | 600 | |
| Number of Tanks | 2 | Unit Depth (External) mm | 690 | |
| Gravity Filtration | No | Net Weight Kg | 73.7 | |
| Pumped Filtration | No | | | |
| Drain Location | Internal | | | |

| Supply Connections | | Shipping | | |
|--|--------|------------------|------|--|
| Requires Installation | Yes | Packed Weight Kg | 87 | |
| Requires Electrical Supply | No | Packed Height cm | 122 | |
| Gas Connection BSP | 1/2" | Packed Width cm | 81.3 | |
| Gas Consumption at full rate Natural m³ per Hour | 2.35 | Packed Depth cm | 68.5 | |
| Gas Pressure Natural mbar | 16.3 | | | |
| Total heat input at full rate Natural kW | 22.79 | | | |
| Total heat input at full rate Natural BTU per hour | 74,000 | | | |

Available Accessories

CH01 NULL

Product Code: J10/N Page Number: 1 Print Date: 20/03/2019





SILVERLINK 600


Available Accessories

CH02 NULL

Technical Picture













Lincat Limited

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of

Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 503250

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm

Print Date: 20/03/2019 Product Code: J10/N Page Number: 3