



# Product Code: LR200 13-112

## Freezer Undercounter Cabinet

---



## Features & Benefits

---

- Front breathing refrigeration system, suitable for use even in enclosed areas
- Easy to use microprocessor control with digital display on the front for easy visual reference
- Stainless steel exterior as standard with aluminium interior
- Roller castors to rear for ease of movement
- Integrated door lock for security
- High quality magnetic door gasket
- Operate in ambient up to 40°C

## External Finish

s/s ext Standard

## Base Fittings

Castors - Rear Fixed Standard

Levelling Bolts Standard

## Electrical, Service & Ecodesign Data

230/50/1 Standard

Fuse Required 13

Global Warming Potential 3922

Energy Efficiency Index 109.45

Refrigerant Charge 0.210

kWh (24 hours) 8.86

## Internal Finish

aluminium Standard

## Doors

Solid Standard

## Specification

Dimensions (Width) 684

Dimensions (Height) 824

Dimensions (Depth) 755

Weight (Unpacked, kg) 84

Weight (Packed, kg) 94.1

Gross Volume 200

Noise DbA @ 1M TBC

## Shelving

Nylon Coated Shelf Option

## Refrigeration

R134a - Industry Standard Standard

Integral Refrigeration System Standard

## Footnotes

- External cabinet depth excludes 25mm door handle
- Note: for airflow, ensure that 25mm clearance is allowed above the cabinet
- Decibel rating measured 1m high from the floor and 1m from the cabinet



## Application

This appliance is intended for use in ambient temperatures up to 40°C

## Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

## Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



Energy



Quality



Value



Design



Hygiene



After Care