

LINCAT SILVERLINK PROPANE GAS COUNTER-TOP SALAMANDER GRILL - W 600 MM - 5.0 KW

MODEL: GR3/P



Sometimes during fast turnaround times, you need to be able to toast and grill at speed. The Silverlink 600 Gas Salamander Grill is ideal for these scenarios. Perfect for any modestly-sized, fast-paced restaurant, pub or takeaway, the grill boasts powerful ceramic plaque burners for rapid heat up, with five shelf positions to give maximum flexibility for all catering operations. Easy to clean, it also comes with a chrome wire shelf to allow trays and food to be placed on for cooking. Producing perfectly grilled meat, fish, and toast has never been as simple or stress-free.

SILVERLINK 600

PRODUCT OPTIONS AND ACCESSORIES

- GR3/BS BENCH STAND FOR GR3 H410,D350,W605
- ABP03 BRANDING PLATE KIT
- CH01 CATERFLEX HOSE 1/2" 1 METRE
- CH02 CATERFLEX HOSE 1/2" 1.5 METRE
- GR3/FS FLOOR STAND FOR GR3 H1260,D350,W605
- GR3/WS WALL SHELF FOR GR3

PRODUCT FEATURES

- Powerful ceramic plaque burners for rapid heat up
- 5 shelf positions to give maximum flexibility for all catering operations
- Chrome wire shelf to allow trays and food to be placed on for cooking
- · Cool touch handles for safety
- Enamelled interior and hood for easy cleaning







LINCAT SILVERLINK PROPANE GAS COUNTER-TOP SALAMANDER **GRILL - W 600 MM - 5.0 KW**

MODEL: GR3/P

WEIGHTS & DIMENSIONS	
Width	600 mil
Depth	423 mil
Height	408 mil
Weight	20.5 kg

SHIPPING DETAILS	
Ship Width	70 cm
Ship Depth	55 cm
Ship Height	49.5 cm
Ship Weight	22.55 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS		
Primary Energy Source Type	Gas	Gas Inlet Size
Kilowatts	5 kW	Gas Inlet Pressure Re
Electrical Connection Type	Not Applicable	Gas Total BTUs
Electrical Plug Type	Not Applicable	Gas Consumption at
Number of Electrical Plugs	Not Applicable	Total Heat Input at M
Gas Type	Propane	Total fleat illput at iv

Gas Inlet Size	0.5 in
Gas Inlet Pressure Required	37 mBar
Gas Total BTUs	17060 BTU
Gas Consumption at Max Use Per Hour	0.36 m ³
Total Heat Input at Max Use	5 kW, 17100 BTU per hour
Energy Saving	No

ADDITIONAL SPECIFICATIONS	
Broiler Base Configuration	Not Applicable
Broiler Type	Salamander
Control Type	Mechanical
Cooking Area Plate Depth	225 mm
Cooking Area Plate Width	410 mm

Food Production Rate	42 x 115g [4oz] burgers [frozen] per hour
Heat Location	Top Only
Heat Source Type	Ceramic
Number of Heating Zones	1
Number of Shelf Positions	4

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 23, 2024










MODEL: GR3/P

TECHNICAL DRAWING







Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 23, 2024

