



Cook with confidence with the Silverlink 600 Electric Oven, which comes with a large capacity fan assisted oven for increased productivity, superior heat distribution and reduced cooking times, and higher power for for reduced heat up to increase efficiency. Ideal for restaurants, takeaways or pubs, the oven, which accommodates 1/1 GN dishes and boasts a rapid cool down feature, guarantees excellent performance and optimum efficiency. Multi-use, there are four shelf positions with two removable shelves, while the oven is also able to support Silverlink 600 counter top units such as boiling tops, bains marie, griddles and work tops.

AIA FILE NUMBER:

PRODUCT OPTIONS AND ACCESSORIES

- SLS7V Lincat Silverlink 600 Free-standing Floor Stand - for V7 Series Ovens - W 750 mm
- V7/T V7 TOP COVER

PRODUCT FEATURES

- Large capacity fan assisted oven for increased productivity. Ideal for use in restaurants, takeaways or pubs
- Higher power for For Reduced heat up times and cooking times, for increased efficiency
- Fan assisted oven for superior heat distribution and reduced cooking times
- Rapid cool down feature
- Accommodates 1/1 gastronorms
- Four shelf positions with two removable shelves
- Able to support Silverlink 600 counter top units such as boiling tops, bains marie, griddles and work tops
- Stainless steel interior with radiused corners and removable side shelf supports for easy cleaning

ITEM NUMBER:

WEIGHTS & DIMENSIONS

Width	750 mil
Depth	600 mil
Height	674 mil
Weight	49.4 kg

SHIPPING DETAILS

Ship Width	91 cm
Ship Depth	80 cm
Ship Height	86 cm
Ship Weight	54.34 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Source Type	Electricity	Number of Electrical Conductor Wires	1
Electrical Amps	17.4	Electrical Connection Type	Direct Hardwired
Electrical Voltage	240 volts	Electrical Plug Type	Hardwired
Electrical Watts	4000	Number of Electrical Plugs	Not Applicable
Electrical Phase	Single	Dedicated Circuit Required	Yes
Kilowatts	4 kW	Energy Saving	No

ADDITIONAL SPECIFICATIONS

Control Type	Mechanical, Rotary Control Knob	Door Type	Solid
Cooking Chamber Depth	335 mm	Fan Assisted	Yes
Cooking Chamber Height	430 mm	Gastronorm Capacity	1 x GN1/1
Cooking Chamber Width	558 mm	Number of Wire Racks	3
Cooking Rack Depth	335 mm	Temperature Maximum	250 °C
Cooking Rack Width	540 mm	Temperature Minimum	50 °C

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

