



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
UP-651 SS UK

19102546

22/06/2023

DENOMINATION:

Professional refrigerated cabinet (stainless steel exterior) with 3 (GN+2/1)+1 shelves.


DESCRIPTION :

- Exterior made of stainless steel.
- Inner body made of ABS food grade material.
- Rounded edges and corners on the inside for easy cleaning.
- Door with built-in handle.
- Reversible door.
- Fitted with key lock as standard.
- Digital thermometer with temperature control.
- Working voltage: 230 V - 50 Hz.
- Guides inbuilt into the sides of the cabinet with anti-tip system.
- Drain inside the chamber.
- Forced refrigeration. Evaporator integrated into the back wall of the cabinet. A fan distributes the cold, obtaining a uniform temperature inside.
- R-600a hydrocarbon refrigerant gas.
- Operational temperature: -1 °C ÷ +6 °C, Ambient temperature 32 °C.
- UK Plug.

POSSIBLE OPTIONS :

- Glass door

DIMENSIONS



X Width	780 mm	X Gross width	820 mm
Y Depth	740 mm	Y Gross depth	780 mm
Z Height	1865 mm	Z Gross height	2010 mm
Net Weight	85,0 kg	Gross Weight	98,0 kg
Net volume	1,076 m3	Gross volume	1,286 m3

ELECTRICITY TECHNICAL SPECIFICATIONS

Amperage (A)	1.3A
Electric frequency	50Hz
Electric power	0,186 kW
Voltage	230V - 1N

GAS TECHNICAL SPECIFICATIONS

Gas type	R-600a
----------	--------

COLD TECHNICAL SPECIFICATIONS

Annual elec. consumption	954,00 kWh
Clasif. Energy efficiency	D
Climate class	4
Cooling gas load	78,000 g
Energy Efficiency Index	65,76 %
Model Type	Vertical cabinet
Power consumption 24h	2,61 kWh
Refrigeration net.vol	511 L
Refrigeration power	0,292 kW

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1,5+T - 6 A
--------------------------	---------------

OTHERS

Condensation system	Static
Number of doors	1

