

VT 75 BIOMEDICAL CHEST FREEZER

-40°C -60°c

BIOMEDICAL

The VT low temperature freezers creates the possibility to maintain temperatures as low as -60°C. Supreme stability, reliability, user-friendliness and ease of cleaning make these freezers an ideal solution for laboratories and hospitals.





DIMENSIONS	VALUE	
Outer Dimensions, HxWxD	870x555x555	
Inner Dimensions, HxWxD	465x390x390	
Weight Gross/Net, kg	48,2 / 42,	
Material Inner Cabinet	Painted Steel	
Material Outer Cabinet	Painted Ste	
Insulation Thickness, mm	8	
Insulation Type	Polyurethane with Cyclopentar	
Mobility / Castors	, , , , , , , , , , , , , , , , , , ,	
Refrigerant, Type	Nature R	
Number of compressors	1	
Internal Air Distribution	Statio	
Number of Probes	1	
CONTROLLER	VALUE	
Controller	XR30CX	
Controller language	No language - only 3 digits	
USB Connection	No.	
Logging	N	
Temperature Graph	N	
High/Low Temp. Alarm	Ye	
Open Door Alarm	N	
Probe Failure Alarm	Ye	
Power Failure Alarm	No	
STORAGE	VALUE	
Volume, Gross/net, L	74	
Baskets		
Basket material	Steel coated with plastic powde	
Inner lids	No.	
FEATURES	VALUE	
Lock	Yes	
LED Light	No	
Battery Backup for Controller, 24h	No	
Porthole	Yes - Ø 12 mm	
Dry Contact	No	
Door	Solid	



VT 75 BIOMEDICAL CHEST FREEZER

The VT low temperature freezers creates the possibility to maintain temperatures as low as -60°C. Supreme stability, reliability, user-friendliness and ease of cleaning make these freezers an ideal solution for laboratories and hospitals.

Frequency	Hz	50Hz
Max Ambient	°C	30°C
Max Humidity	% rh	55%
PERFORMANCE	UNIT	VALUE
All data in RT20°C		
Temperature Range	°C	Fra -40 til -60
Uniformity in performance - difference +/- from Avg set point	°C	-
Pull down time (from 25 to fabric setpoint)	Minutes	-
Hold over time (From fabric SP to -25, -40 and -60) Empty	Minutes	-
Refrigerant		Nature R
Number of probes	pcs	1
Defrost	y/n	No
Internal air distribution		Static
Number of compressors	pcs	1
Safety thermostat	y/n	No
Energy 24 hours	kWh/24h	-
Energy year	kWh/year	-